industries technical waterproofing solutions

ck 86/23380/23. darachem house, 6 mission road, anderbolt, boksburg north. p.o. box 6008 dunswart 1508. tel: (011) 892 2917/8/9, fax: (011) 892 1519. email: info@darachem.co.za

GALV-CLEANGalvinisedironcleaner

Discussion

GALV-CLEAN is a new generation water rinsable, galvanised iron cleaner used to clean and degrease new and or weathered galvanised steel, for use in conjunction with **SUPAROOF** roof paint. **GALV-CLEAN** is a very effective Steel and galvanised steel surfaces must be free of loose paint, grease, grime, oil and rust. For use on new and weathered galvanised steel. It's slightly abrasive properties effectively remove the manufacturer's greasy protective layer and the product's slight pigmentation makes it easy to see where it has been applied.

Physical Properties

Colour: Light Red

Pack Size: 5L and 20L

Application: Brush or Block Brush

Application Time: Do not apply before 09:00 and after 16:00 in the winter.

Coverage: 10 – 12L/m²

Cleaning: Water

Flammability: Flammable

Application

Mixing:

Before use, stir well, using a flat paddle.

New Metal Application:

Using a brush or block brush, apply a generous coat of **GALV-CLEAN** to all areas needing degreasing. Using a roller is not recommended. Vigorously work the material into the surface.

Allow a full 20 minutes standing time, before thoroughly washing the treated surface with a high-pressure hose or copious amounts of fresh water. Repeat the process until the surface is water-break (grease) free. Once the surface is dry, apply one or two coats of **DARACRYL DC4** metal primer.

GALV-CLEAN Updated February 2025 page 1



ck 86/23380/23. darachem house, 6 mission road, anderbolt, boksburg north. p.o. box 6008 dunswart 1508. tel: (011) 892 2917/8/9, fax: (011) 892 1519. email: info@darachem.co.za

Thinning **GALVE-CLEAN** will reduce its efficiency.

This product should never be mixed with other products.

Do not apply before 09:00 and after 16:00 in the winter.

Do not apply if rain is imminent.

Clean up with water.

Maintenance

No maintenance required.

Health and Safety

Caution – GALV-CLEAN galvanised iron cleaner is flammable; do not expose to naked flame.

- · Avoid contact with skin or eyes.
- Keep out of reach of children.
- If accidently swallowed, seek medical advice immediately.
- To avoid the risk of spillage, always store and transport containers in a secure upright position.
- Refer to Material Safety Data Sheet for additional information.

Standard Disclaimer

The recommendations contained herein are given in good faith and meant to guide the specifier or user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable. No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond STT Sales (PTY) LTD control.

Where other products are to be used in conjunction with this material, the relevant technical data sheets should be consulted to determine total requirements.

Important Note; It is the responsibility of the user to ensure that the latest TDS is being used for reference. **DARACHEM** Data Sheets are available on our website www.darachem.co.za or Email info@darachem.co.za.

Updated February 2025 (This supersedes all previous publications).

GALV-CLEAN
Updated February 2025
page 2